

EAN: 6414150071256

www.oras.com/en/products/oras/product/2814F-102



- Green Building
- Touchless, Battery-operated, Green Building
- Deck mounted
- Chrome
- Temperature control handle
- Litter filter(s)
- Autofocus infrared sensor, Solenoid valve, Low battery indicator

Technical data

Flow properties

Flow-rate at 300 kPa (with flow controller) **0.028 l/s**

Technical properties

Hot water supply **max. +70°C**
 Working pressure **100 - 1000 kPa**

Software settings


Afterflow period **2 s ± 1 s**
 Max. flow period **2 min**

Electronic properties


Battery **Lithium 2CR5 6 V**

Regulations

EMC Directive **CE 2004/108/EY**
 EN standard **EN 15091**
 Noise class **I (ISO 3822)**
 Protection class **IP 55**



Spare parts



SP2814F-102

	Name	Code
01	Battery casing	199417V
02	Lithium battery, 2CR5 6 V	198330
03	Temperature control handle	600493V
04	Membrane support ring	199205V
05	Solenoid valve	199206V
06	Sensor, 6 V	600659V
07	Aerator, M24x1 , -102	601255V
08	Litter filters	199257/2
09	One-way valve with litter screen	198473/2
10	Gasket, 8x14.3x2	600705/10
11	Temperature regulator	199201V
12	Cover plug	601141V